

SUS316L TPA

溶接管

外径		厚さ		長さ
13.8	×	2.0	×	4000
17.3	×	2.0	×	4000
		2.5	×	4000
		3.0	×	4000
21.7	×	2.0	×	4000
		2.0	×	6000
		2.5	×	4000
		2.5	×	6000
		3.0	×	4000
27.2		3.0	×	6000
	×	2.0	×	4000
		2.0	×	6000
		2.5	×	4000
		2.5	×	6000
34.0		3.0	×	4000
		3.0	×	6000
	×	2.0	×	4000
		3.0	×	4000
		4.0	×	6000
42.7		4.0	×	6000
	×	2.0	×	4000
		3.0	×	4000
		3.0	×	6000
		3.5	×	4000
48.6		3.5	×	6000
		4.0	×	4000
		4.0	×	6000
	×	1.5	×	4000
		2.0	×	4000
	3.0	×	4000	
	3.0	×	6000	

外径		厚さ		長さ
48.6	×	3.5	×	4000
		3.5	×	6000
		4.0	×	4000
		4.0	×	6000
		5.1	×	4000
		5.1	×	6000
60.5	×	2.0	×	4000
		3.0	×	4000
		3.0	×	6000
		3.5	×	4000
		3.5	×	6000
		4.0	×	4000
		4.0	×	6000
		5.5	×	4000
		5.5	×	6000
76.3	×	2.0	×	4000
		3.0	×	4000
		3.0	×	6000
		3.5	×	4000
		4.0	×	4000
		5.2	×	4000
		5.2	×	6000
		7.0	×	4000
		7.0	×	6000
89.1	×	2.0	×	4000
		3.0	×	4000
		3.0	×	6000
		4.0	×	4000
		4.0	×	6000
		5.5	×	4000
		5.5	×	6000
		7.6	×	4000
		7.6	×	6000
101.6	×	2.0	×	4000
		3.0	×	4000
		4.0	×	4000
		5.7	×	4000
		8.1	×	4000
114.3	×	2.0	×	4000
		3.0	×	4000
		3.0	×	6000
		4.0	×	4000

外径		厚さ		長さ
114.3	×	4.0	×	6000
		6.0	×	4000
		6.0	×	6000
		8.6	×	4000
		8.6	×	6000
	139.8	×	3.0	×
		3.0	×	6000
		3.5	×	4000
		3.5	×	6000
		4.0	×	4000
		4.0	×	6000
		5.0	×	4000
		5.0	×	6000
		6.6	×	4000
		6.6	×	6000
		9.5	×	4000
		9.5	×	6000
165.2	×	3.0	×	4000
		3.5	×	4000
		3.5	×	6000
		4.0	×	4000
		5.0	×	4000
		5.0	×	6000
		7.1	×	4000
		7.1	×	6000
		11.0	×	4000
		11.0	×	6000
216.3	×	3.0	×	4000
		3.0	×	6000
		4.0	×	4000
		4.0	×	6000
		4.0	×	6000
		6.5	×	4000
		6.5	×	6000
		8.2	×	4000
267.4		12.7	×	4000
		12.7	×	6000
	×	3.0	×	4000
		4.0	×	4000
		4.0	×	6000
	6.5	×	4000	
	6.5	×	6000	
	9.3	×	4000	

