

# SUS316 TPA

## 溶接管

外径		厚さ		長さ
10.5	×	2.0	×	4000
13.8	×	1.5	×	4000
		2.0	×	4000
		3.0	×	4000
17.3	×	1.5	×	4000
		2.0	×	4000
		2.5	×	4000
21.7	×	2.0	×	4000
		2.5	×	4000
		3.0	×	6000
27.2	×	2.0	×	4000
		2.0	×	6000
		2.5	×	4000
		2.5	×	6000
		3.0	×	6000
34.0	×	2.0	×	4000
		3.0	×	4000
		3.0	×	6000
		3.5	×	4000
		3.5	×	6000
		4.0	×	4000
42.7	×	2.0	×	4000
		3.0	×	4000
		3.0	×	6000
		3.5	×	4000
		4.0	×	4000
48.6	×	2.0	×	4000
		3.0	×	4000
		3.0	×	6000

外径		厚さ		長さ
48.6	×	3.5	×	4000
		3.5	×	6000
		4.0	×	4000
		4.0	×	6000
		5.1	×	4000
		5.1	×	6000
60.5	×	2.0	×	4000
		3.0	×	4000
		3.0	×	6000
		3.5	×	4000
		3.5	×	6000
		4.0	×	4000
		4.0	×	6000
		5.5	×	4000
		5.5	×	6000
76.3	×	2.0	×	4000
		3.0	×	4000
		3.5	×	4000
		3.5	×	6000
		4.0	×	4000
		5.2	×	4000
		5.2	×	6000
		7.0	×	6000
89.1	×	2.0	×	4000
		3.0	×	4000
		3.0	×	6000
		4.0	×	4000
		5.5	×	4000
		7.6	×	6000
101.6	×	2.0	×	4000
		3.0	×	4000
		4.0	×	4000
		5.7	×	4000
		8.1	×	4000
114.3	×	2.0	×	4000
		3.0	×	4000
		3.0	×	6000
		4.0	×	4000

外径		厚さ		長さ
114.3	×	4.0	×	6000
		6.0	×	4000
		6.0	×	6000
		8.6	×	4000
		8.6	×	6000
		139.8	×	3.0
139.8	×	3.0	×	6000
		3.5	×	4000
		3.5	×	6000
		4.0	×	4000
		5.0	×	4000
		5.0	×	6000
		6.6	×	4000
		9.5	×	4000
		165.2	×	3.0
3.0	×			6000
3.5	×			4000
3.5	×			6000
4.0	×			4000
5.0	×			4000
5.0	×			6000
7.1	×			4000
7.1	×			6000
11.0	×			4000
216.3	×	11.0	×	6000
		3.0	×	4000
		4.0	×	4000
		4.0	×	6000
		6.5	×	4000
		6.5	×	6000
		8.2	×	4000
		8.2	×	6000
		12.7	×	4000
		12.7	×	6000
267.4	×	3.0	×	4000
		4.0	×	4000
		4.0	×	6000
		6.5	×	4000
		6.5	×	6000
		15.1	×	6000

