

SUS316 TPA 溶接管

外径	厚さ	長さ
10.5	× 2.0	× 4000
13.8	× 1.5	× 4000
	× 2.0	× 4000
	× 3.0	× 4000
17.3	× 2.0	× 4000
	× 2.5	× 4000
	× 3.0	× 4000
21.7	× 2.0	× 4000
	× 2.5	× 4000
	× 3.0	× 4000
	× 3.0	× 6000
27.2	× 2.0	× 4000
	× 2.0	× 6000
	× 2.5	× 4000
	× 2.5	× 6000
	× 3.0	× 4000
	× 3.0	× 6000
	× 3.9	× 4000
34.0	× 2.0	× 4000
	× 3.0	× 4000
	× 3.0	× 6000
	× 3.5	× 4000
	× 3.5	× 6000
	× 4.0	× 4000
	× 4.5	× 4000
42.7	× 2.0	× 4000
	× 3.0	× 4000
	× 3.0	× 6000
	× 3.5	× 4000
	× 4.0	× 4000
48.6	× 2.0	× 4000
	× 3.0	× 4000

外径	厚さ	長さ
48.6	× 3.0	× 6000
	× 3.5	× 4000
	× 3.5	× 6000
	× 4.0	× 4000
	× 4.0	× 6000
	× 5.1	× 4000
	× 5.1	× 6000
60.5	× 2.0	× 4000
	× 3.0	× 4000
	× 3.0	× 6000
	× 3.5	× 4000
	× 3.5	× 6000
	× 4.0	× 4000
	× 4.0	× 6000
76.3	× 2.0	× 4000
	× 3.0	× 4000
	× 3.5	× 4000
	× 3.5	× 6000
	× 4.0	× 4000
	× 5.2	× 4000
	× 5.2	× 6000
89.1	× 2.0	× 4000
	× 3.0	× 4000
	× 3.0	× 6000
	× 4.0	× 6000
	× 4.0	× 6000
	× 5.5	× 4000
	× 5.5	× 6000
101.6	× 2.0	× 4000
	× 3.0	× 4000
	× 4.0	× 4000
	× 5.7	× 4000
	× 8.1	× 4000
114.3	× 2.0	× 4000
	× 3.0	× 4000
	× 3.0	× 6000

外径	厚さ	長さ
114.3	× 4.0	× 4000
	× 4.0	× 6000
	× 6.0	× 4000
	× 6.0	× 6000
	× 8.6	× 4000
	× 8.6	× 6000
139.8	× 3.0	× 4000
	× 3.0	× 6000
	× 3.5	× 4000
	× 3.5	× 6000
	× 4.0	× 4000
	× 5.0	× 4000
	× 5.0	× 6000
165.2	× 3.0	× 4000
	× 3.0	× 6000
	× 3.5	× 4000
216.3	× 3.5	× 6000
	× 4.0	× 4000
	× 5.0	× 4000
	× 5.0	× 6000
	× 7.1	× 4000
	× 7.1	× 6000
	× 11.0	× 4000
	× 11.0	× 6000
	× 3.0	× 4000
	× 4.0	× 4000
	× 4.0	× 6000
267.4	× 6.5	× 4000
	× 6.5	× 6000
	× 8.2	× 4000
	× 8.2	× 6000
	× 12.7	× 4000
	× 12.7	× 6000
	× 3.0	× 4000
267.4	× 4.0	× 4000
	× 4.0	× 6000
	× 6.5	× 4000
	× 6.5	× 6000
267.4	× 9.3	× 4000
	× 9.3	× 6000

