

## SUS316L TPA

### 溶接管

外径		厚さ		長さ
13.8	×	2.0	×	4000
17.3	×	2.0	×	4000
		2.5		4000
		3.0		4000
21.7	×	2.0	×	4000
		2.0		6000
		2.5		4000
		2.5		6000
		3.0		4000
		3.0		6000
		3.7		4000
27.2	×	2.0	×	4000
		2.0		6000
		2.5		4000
		2.5		6000
		3.0		4000
		3.0		6000
		3.9		4000
34.0	×	2.0	×	4000
		3.0		4000
		3.0		6000
		3.5		4000
		3.5		6000
		4.0		4000
		4.0		6000
42.7	×	2.0	×	4000
		3.0		4000
		3.0		6000
		3.5		4000
		4.0		4000
48.6	×	1.5	×	4000

外径		厚さ		長さ
48.6	×	2.0	×	4000
		3.0		4000
		3.0		6000
		3.5		4000
		3.5		6000
		4.0		4000
		4.0		6000
		5.1		4000
60.5	×	2.0	×	4000
		3.0		4000
		3.0		6000
		3.5		4000
		3.5		6000
		4.0		4000
		4.0		6000
76.3	×	2.0	×	4000
		3.0		4000
		3.0		6000
		3.5		4000
		4.0		4000
		5.2		4000
		5.2		6000
89.1	×	2.0	×	4000
		3.0		4000
		3.0		6000
		4.0		4000
		4.0		6000
		5.5		4000
		5.5		6000
101.6	×	2.0	×	4000
		3.0		4000
		4.0		4000
		5.7		4000
		8.1		4000
		8.1		4000
114.3	×	2.0	×	4000

外径		厚さ		長さ
114.3	×	3.0	×	4000
		3.0		6000
		4.0		4000
		4.0		6000
		6.0		4000
		6.0		6000
		8.6		4000
		8.6		6000
139.8	×	3.0	×	4000
		3.0		6000
		3.5		4000
		3.5		6000
		4.0		4000
		4.0		6000
		5.0		4000
		5.0		6000
165.2	×	3.0	×	4000
		3.5		4000
		3.5		6000
		4.0		4000
		5.0		4000
		5.0		6000
216.3	×	3.0	×	4000
		3.0		6000
		4.0		4000
		4.0		6000
		6.5		4000
		6.5		6000
267.4	×	3.0	×	4000
		4.0		4000
		4.0		6000
		4.0		6000

